## Wall Stay Fixing



Connection Size		
Valve to Radiator	N/A	
Valve to Pipe	N/A	

Allen Key size	
To adjust Lock-Shield	N/A
To fit Coupler to Radiator	N/A
Allen Keys are not included	

Pressure Ratings		
Max Test Pressure	N/A	
Max Operating Pressure	N/A	
Max Differential Pressure	N/A	
Pressure Drop Value (Kvs)	N/A	

Kvs value is the metric measure for the flow of a fully opened valve. It is defined as: The volume flow in cubic metres per hour of water at a temperature of between 5° and 40° Celsius with a pressure drop across the valve of 1 bar.

Available Finishes - Wall Stays		
Brass	Antique Brass	
Un-Lacquered Brass	Black	
Chrome	Antique Copper	
Brushed Copper	Polished Copper	
Nickel	Satin Nickel	

These valves have a highly polished finish. The Un-lacquered Brass are highly polished as new but will tarnish and age naturally over time.

Available Finishes - Wall Stays		
Pewter		

These valves are un-lacquered and designed to look old. They are hand finished and appearance may vary from one valve to the next

Flow Ratings		
Normal Flow Rate	N/A	
Max Flow Rate	N/A	

Temperature Ratings		
Max Test Temperature	N/A	
Max Operating Temperature	N/A	
Temperature Adjustment Range	N/A	

## Disclaimer

All dimensions are approximate and for roughing in only. We reserve the right to alter dimensions without notice. We recommend no work be carried out until the goods arrive. We can take no responsibility for errors in information supplied.

